

Home Energy Storage Battery

Ehome-LFP 5000








UN38.3



WHITE

Key Features

- Assembly freely in series or parallel Up to 8pcs
- High energy efficiency Energy efficiency (charge and discharge) > 97%
- High Rate Charge & Discharge Max charge current 30A, Max discharge current 40A
- More Safety Dual hardware & Triple software protection
- Safe and Reliable BMS Relay design instead of mosfet
- Long Life Reliable LFP cells, Cycle life >6000 cycles
- High Reliability Key devices (Relay, Fuse) approved by UL and IEC
- More Smart With digital monitor system App with WIFI
- Smart Design & Easy installation Plug in & off
- More Quiet Without fan, more quiet and reduce the risk of fan failure





Model		Ehome-LFP 5000
Total Energy*		5.1kWh
Usable Energy(DC)*		4.8kWh
Nominal Dis-/Charge Power		3.0kW
Peak Power(Only Discharge)		3kW for 3s
Constant Current(Only Discharge)		80A
Voltage		48~56Vd.c
Nominal Voltage		51.2Vd.c
Nominal Current		60A
Max. Charge Voltage		57.6Vd.c
Weight		45kg
Dimension(mm)		500*448*135mm
Max.recommended DOD		90%
Operating Condition		Indoor
Operating Temperature	Charge	From 0~50°C
	Discharge	From -10~55°C
WIFI Frequency Range		2400MHz~2483MHz
Humidity		< 60%(No condensed water)
Over Voltage Category		II
Cooling Type		Natural cooling
Case Material		Metal
Color		Black or White
Installation		Wall mounting/Ground Installation
IP rating		IP 20
Protective Class		I
Max. Connection Number		8S/4P
Warranty		10 years
Life Span		> 15 years
Communication		CAN/ RS485
Protection Mode		Dual hardware protection
Battery Protection		Over-current/Over-voltage/Short circuit/ Under-voltage/Over temperature
Safety		Cell UL 1973
		CE
Hazardous Material Classification		9
Transportation		UN 38.3

Made By Omnis Power USA Inc.

*Total Energy/Usable Energy measured under specific conditions from OMNISPOWER 0.2C CC-CV

Testing conditions based on temperature 25 $^{\circ}\text{C}$ at the beginning of life.